



**American Power Cord, Type B, UL certified 3 pins
NEMA 5-15P Plug to IEC 60320 C13 Connector**

Plug and Connector Type: B
Non-rewirable With Earthing Contact, Moulded.

Fully conforms to the NEMA 5-15P, IEC 60320 C13 plug standards and RoHS, REACH and PAHS compliant. Quality is stable and reliable!

- Electrical Rating: 10A
- Voltage: 125V
- Approvals: UL Certified

American UL Power Cords

Specifications

Label	Value
Approvals:	UL
Plug / Connector Type:	B
Connector Standard:	NEMA 5-15P, IEC 60320 C13
Maximum Current rating:	10A
Maximum Voltage:	125V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity

Available Wire Styles

Gauge/ # Conductors	Cord Type
3Cx18AWG, 3Cx16AWG	SPT-2, SPT-3
3Cx18AWG, 3Cx16AWG	HPN
3Cx18AWG	SVT, SVTO, SVTOO
3Cx18AWG, 3Cx16AWG, 3Cx14AWG, 3CX12AWG	SPT-3, SJT, SJTO, SJTW, SJTOO, SJTOW, SJTOOW

Our other certificated products

