



**Australia Power Cord, Type C20, SAA, RCM certified
3 pins IEC 60320 C20 Connector Plug**

Plug and Connector Type: C20
Non-rewirable With Earthing Contact, Moulded.

Fully conforms to the IEC 60320 C20 plug standards and RoHS, REACH and PAHS compliant. Quality is stable and reliable!

- Electrical Rating: 16A
- Voltage: 250V
- Approvals: SAA, RCM Certified

Australia SAA Power Cords

Specifications

Label	Value
Approvals:	SAA, RCM
Plug / Connector Type:	C20
Connector Standard:	IEC 60320 C20
Maximum Current rating:	16A
Maximum Voltage:	250V
Number of Poles and Wires:	3 poles, 3 wires
Copper Conductor Material:	Oxygen free Copper (OFCU)
Outer Jacket Material:	PVC, Rubber, Halogen-Free, Textile braid
Blade Material:	Nickel coated Brass
Flamability Rating:	UL 94V-0
Color:	black is standard but any color available
Temperature Rating:	minus 40C though plus 75C
Environmental Certifications:	RoHS, REACH, PAHs
Testing:	Hi-Pot (Dielectric Withstanding Voltage), Polarity (pinout) and Continuity

Available Wire Styles

Gauge/ # Conductors	Cord Type
3X0.75mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.0mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F
3x1.5mm ²	4V-75, H05VV-F, H05RR-F, H05RN-F, H07RN-F

Our other certificated products

